

## Product Highlights

- Platform capacity up to 240kg (529lbs)
- Easily passes through standard doors and can access elevators
- Exclusive open chassis reduces daily maintenance time
- DC motor drive, giving a longer runtime

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

# SINOBOOM

Sinoboom Intelligent Equipment Pty Ltd

📍 50/358 Clarendon St  
South Melbourne VIC, 3205

🌐 [www.sinoboom.com](http://www.sinoboom.com)

✉ [sales@sinoboom.com](mailto:sales@sinoboom.com)

# Electric Series Scissor Lifts

## 0407SE (1330SE)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Model		0407SE (1330SE)	
Dimension		Metric	US
Max Working Height		5.8m	19'
A Max Platform Height		3.8m	12'6"
B Max Horizontal Extension		0.6m	23.6"
C Length-Stowed		1.42m	4'8"
D Width-Stowed		0.76m	2'6"
Height - stowed	Rail Folded	1.67m	5'6"
	E Rail Unfolded	1.97m	6'6"
	Fixed Rail	1.97m	6'6"
F Wheelbase		1.11m	3'8"
Ground Clearance (Pothole Guard Stowed)		65mm	2.5"
Ground Clearance (Pothole Guard Deployed)		20mm	0.75"
Platform Dimensions (LxWxH)		1.34m x 0.7m x 1.1m	4'5" x 2'4" x 3'7"
Performance			
Platform Allowable Occupants (Indoor)		2 persons (Indoor Only)	
Platform capacity		240kg	529lbs
Lift Extension Capacity		100kg	220lbs
Drive Speed-Stowed		4km/h	2.5mph
Drive Speed-Raised		0.8km/h	0.5mph
Lift Time (Unloaded)		30s-33s	
Descent Time(Unloaded)		25s-30s	
Gradeability		25%	
Turning Radius (Inside/Outside)		0.3m/1.35m	12"/4'5"
Tilt Rating (Front to Back/Side to Side)		3°/1.5°	
Tyres-solid		230x80mm	9x3"
Power			
Batteries		12Vx2/115Ah	
Power Source		24V DC	
Drive Mode		Motor, Rear wheel	
Charger Input		100-240V AC	
Charger Output		15A	
Hydraulic System Capacity		5L	1.1gal
Weight			
Weight (Indoor)		880kg	1,940lbs
Standards Compliance		ISO/CE/ANSI/CSA/AS/CU-TR	

